

Permabond®

Engineering Adhesives

SAFETY DATA SHEET

Permabond UV612

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Permabond UV612

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Permabond Engineering Adhesives Ltd.
Wessex Way
Colden Common
Winchester
Hampshire. SO21 1WP
United Kingdom
Tel: +44 (0)1962 711 661
Fax: +44 (0)1962 711 662
info.europe@permabond.com

1.4. Emergency telephone number

Emergency telephone UK +44 (0)1962 711 661 USA 0800 640 7599 Asia +86 (0)21 5773 4913

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H335

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xi;R36/37/38. R43.

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Permabond UV612

Precautionary statements	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352a IF ON SKIN: Wash with plenty of soap and water P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/ attention.
Contains	2-ETHYLHEXYL METHACRYLATE, 2-HYDROXYETHYL METHACRYLATE
Supplementary precautionary statements	P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/container in accordance with existing Community, National and local regulations.

2.3. Other hazards

None under normal conditions.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

2-ETHYLHEXYL METHACRYLATE 10-30%		
CAS number: 688-84-6	EC number: 211-708-6	REACH registration number: 01-2119490166-35-XXXX
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H335 Aquatic Chronic 3 - H412	Classification (67/548/EEC or 1999/45/EC) Xi;R36/37/38.	
2-HYDROXYETHYL METHACRYLATE 10-30%		
CAS number: 868-77-9	EC number: 212-782-2	REACH registration number: 01-2119490169-29-XXXX
Classification Eye Irrit. 2 - H319 Skin Sens. 1 - H317	Classification (67/548/EEC or 1999/45/EC) R43 Xi;R36/38	
METHYL METHACRYLATE <1%		
CAS number: 80-62-6	EC number: 201-297-1	REACH registration number: 01-2119452498-28-XXXX
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Skin Sens. 1 - H317 STOT SE 3 - H335	Classification (67/548/EEC or 1999/45/EC) F;R11 R43 Xi;R37/38	

Permabond UV612

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water. If symptoms develop, obtain medical attention
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	Skin irritation. Mild dermatitis, allergic skin rash.
Eye contact	Irritating and may cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. Treat symptomatically.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products	Burning produces irritating, toxic and obnoxious fumes. Carbon monoxide, carbon dioxide, and unknown hydrocarbons.
--------------------------------------	--

5.3. Advice for firefighters

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Absorb spillage with sand or other inert absorbent. Transfer to suitable, labelled containers for disposal.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. For waste disposal, see section 13.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Permabond UV612

Usage precautions Avoid contact with skin and eyes. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C. Protect against direct sunlight. Never return unused material to storage receptacle.

7.3. Specific end use(s)

Specific end use(s) Adhesive.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

METHYL METHACRYLATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield. Personal eye protection should conform to EN 166

Hand protection

Nitrile rubber or Viton™ gloves are recommended. Cotton or other absorbent gloves should not be worn. Gloves should conform to EN 374. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Other skin and body protection

Employee must wear appropriate protective clothing and equipment to prevent any possibility of skin contact with this substance.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke. Use of good industrial hygiene practices is required.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Colourless.
Odour	Acrylic
Odour threshold	Not available.
pH	Not relevant.
Melting point	Not available.

Permabond UV612

Initial boiling point and range	Not applicable.
Flash point	>100°C
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.94
Solubility(ies)	Slightly soluble in water. Soluble in the following materials: Organic solvents.
Auto-ignition temperature	Not available.
Viscosity	≈550 mPa s @ 23°C
Oxidising properties	Not available.
9.2. Other information	
Other information	Not relevant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The following materials may react with the product: Strong oxidising agents. Light.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions There are no known reactivity hazards associated with this product.

10.4. Conditions to avoid

Conditions to avoid Protect against direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong reducing agents. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified organic compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects The toxicological properties of this product have not been fully evaluated. Avoid direct contact with skin or eyes. Do not ingest or inhale.

Skin sensitisation

Skin sensitisation May cause sensitisation by skin contact.

Aspiration hazard

Aspiration hazard None under normal conditions.

Permabond UV612

Inhalation	May cause respiratory system irritation.
Skin contact	Irritating to skin.
Eye contact	Irritating to eyes.

Toxicological information on ingredients.

2-ETHYLHEXYL METHACRYLATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,000.1

Species Rat

ATE oral (mg/kg) 2,000.1

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

2-HYDROXYETHYL METHACRYLATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,000.0

Species Rabbit

ATE dermal (mg/kg) 3,000.0

METHYL METHACRYLATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE dermal (mg/kg) 5,000.0

Acute toxicity - inhalation

Permabond UV612

Acute toxicity inhalation 29.8
(LC₅₀ vapours mg/l)

Species Rat

ATE inhalation (vapours 29.8
mg/l)

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

SECTION 12: Ecological Information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Toxicity No data available.

Ecological information on ingredients.

2-ETHYLHEXYL METHACRYLATE

Acute toxicity - fish EC₅₀, 96 hours: 2.78 mg/l, *Oryzias latipes* (Red killifish)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 4.56 mg/l, *Daphnia magna*

Acute toxicity - aquatic plants EC₅₀, 72 hours: 7.68 mg/l, *Selenastrum capricornutum*
NOEC, 72 hours: 0.28 mg/l, *Selenastrum capricornutum*

Acute toxicity - microorganisms NOEC, 28 days: 100 mg/l, Activated sludge

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 0.11 mg/l, *Daphnia magna*

2-HYDROXYETHYL METHACRYLATE

Acute toxicity - fish LC₅₀, 96 hours: > 100 mg/l, *Oryzias latipes* (Red killifish)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 380 mg/l, *Daphnia magna*

Acute toxicity - aquatic plants EC₅₀, 72 hours: 836 mg/l, *Selenastrum capricornutum*
NOEC, 72 hours: 400 mg/l, *Selenastrum capricornutum*

Acute toxicity - microorganisms EC₅₀, 16 hours: > 3000 mg/l, *Pseudomonas fluorescens*

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 24.1 mg/l, *Daphnia magna*

METHYL METHACRYLATE

Acute toxicity - fish LC₅₀, 96 hours: > 79 mg/l, *Onchorhynchus mykiss* (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 69 mg/l, *Daphnia magna*

Permabond UV612

Acute toxicity - aquatic plants	NOEC, 72 hours: > 110 mg/l, Selenastrum capricornutum EC ₅₀ , 72 hours: > 100 mg/l, Selenastrum capricornutum
Acute toxicity - microorganisms	EC ₂₀ , 30 minutes: 150 - 200 mg/l, Activated sludge
Chronic toxicity - fish early life stage	NOEC, 35 days: 9.4 mg/l, Danio rerio (Zebrafish)
Chronic toxicity - aquatic invertebrates	NOEC, 21 days: 37 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability No data available.

Ecological information on ingredients.

2-ETHYLHEXYL METHACRYLATE

Biodegradation Water - Degradation 88%: 28 days

2-HYDROXYETHYL METHACRYLATE

Biodegradation Water - Degradation 84%: 28 days

METHYL METHACRYLATE

Biodegradation Water - Degradation 94%: 14 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Ecological information on ingredients.

2-HYDROXYETHYL METHACRYLATE

Bioaccumulative potential BCF: 1.34 - 1.54,

12.4. Mobility in soil

Mobility No data available. The product has poor water-solubility.

Ecological information on ingredients.

2-HYDROXYETHYL METHACRYLATE

Adsorption/desorption coefficient Water - Koc: 42.7 @ 20°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Permabond UV612

General information	Waste disposal should be in accordance with existing Community, National and local regulations Empty containers may contain product residue; follow SDS and label warnings even after they have been emptied.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances.

SECTION 14: Transport information

General The product is not classified as dangerous for carriage.

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Not classified.

Transport labels

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

**Annex II of MARPOL 73/78
and the IBC Code**

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Guidance Workplace Exposure Limits EH40.
CHIP for everyone HSG228.
Safety Data Sheets for Substances and Preparations.
Approved Classification and Labelling Guide (Sixth edition) L131.

Permabond UV612

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	11/08/2016
Revision	4
Supersedes date	22/03/2016
Risk phrases in full	R36/37/38 Irritating to eyes, respiratory system and skin. R36/38 Irritating to eyes and skin. R43 May cause sensitisation by skin contact.
Hazard statements in full	H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.