



MOLYKOTE®

FROM DOW CORNING

Semi-dry Lubricants



AV04061

Optimal performance, better for the environment

Molykote® Semi-dry Lubricants

Meeting Performance and Environmental Needs

When it comes to providing high performance, reliability, flexibility of design and value in increasingly sophisticated home electronics products, designers and engineers around the world turn to Dow Corning for Molykote® lubrication solutions.

Ordinary lubricants often cannot meet the technical demands of today's sophisticated home electronics products, nor the concerns of an increasingly environmentally sensitive industry, but Molykote Semi-dry lubricants provide trouble-free performance on a variety of substrates.


Molykote® Semi-dry Lubricants provide the following:

- **Wide temperature range** – Maximum temperature range you can choose is -60° to 150° C.
- **Clean lubricants** – Transparent, dry, non-sticky thin film coating without dust.
- **Good compatibility** – Compatible with elastomers and plastics.
- **Environmental Friendly** – Zero Ozone Depletion Potential (ODP). The Global Warming Potential (GWP) is lower than other equivalent Molykote products.
- **Easy to apply** – You can apply with a brush or by dipping. No application machine required.

The characteristics of each product are shown in the chart in the opposite page. Select a product that best meets your needs. If you have more specific needs, we can tailor a solution to meet your needs exactly.

Here are some application examples:

- **CD and DVD Players** – Molykote lubricants are ideal for guide bars, screw gears, lead screw, and plastic actuators in CD and DVD players because they are compatible with plastic, reduce noise, and prevent oil spreading
- **Mobile Phones** – Plastic-compatible Molykote lubricants help mobile phone hinges and sliding parts move effortlessly.
- **Camcorders** – Dry and invisible Molykote lubricants provide torque stability and plastic compatibility for camcorders parts, such as auto focus, actuators and hinges.
- **Digital Cameras** – Invisible Molykote lubricants support even the most precise digital camera parts and functions, such as the auto focus, shutter and dial switch
- **Card Slot** – Semi-dry lubricants provide product life-long lubrication



PROPERTY	PD-930	L-8001	L-8011	L-8033
Appearance	White	White	White	Pink
Temperature range (°C)	-60 ~ 150	-60 ~ 120	-60 ~ 120	-60 ~ 150
Specific gravity	1.49	1.43	1.45	1.46
Flash point (°C)	None	None	None	None
Non-volatile contents (%)	10.0	6.0	2.6	6.0
Plastic compatibility test (1/4 oval test) POM, PS, ABS	No crack	No crack	No crack	No crack
Coefficient of friction (PS vs POM)	0.08	0.07	0.06	0.08
Coefficient of friction (STEEL vs POM)	0.08	0.11	0.06	0.08
Package size	1kg	1kg	1kg	1kg



AV10940

* Please note that glass bottles are samples to show the product appearance, not sold commercially in this size.

How To Contact Us

Dow Corning has sales offices, manufacturing sites, as well as science and technology laboratories around the globe. For more information, visit www.dowcorning.com or www.molykote.com, or call one of our primary locations listed here.

Your Global Connection

The Americas

World Headquarters (United States)

TEL: + 1 989 496 6000

Technical Information Center

TEL: + 1 800 248 2481

Brazil

Dow Corning do Brasil Ltda.

TEL: + 55 11 3759 4300

Asia

Asia Headquarters (Japan)

TEL: + 81 3 3287 8300

FAX: + 81 3 3287 1088

China

TEL: + 86 21 2306 5500

FAX: + 86 21 6351 2600

Technical Information Center

TEL: + 86 21 3774 7110

Toll free: 400 880 7110

India

TEL: + 91 22 6694 6868

FAX: + 91 22 6694 6848

Korea

TEL: + 82 2 551 7600

FAX: + 82 2 551 6400

Singapore

TEL: + 65 6253 6611

FAX: + 65 6253 6070

Thailand

TEL: + 66 2634 7078

FAX: + 66 2634 7076

Australia & New Zealand

Dow Corning Australia Pty Ltd.

TEL: + 61 1300 360 732

Europe

European Headquarters (Belgium)

Dow Corning S.A.

TEL: + 32 64 88 80 00

Germany

Dow Corning GmbH

Technical Information Center

TEL: + 49 611 237 964

France

Dow Corning France S.A.

Sales Office

TEL: + 33 47 284 1360

Italy

Dow Corning S.p.A.

Sales Office

TEL: + 39 0298 8321

Spain

Dow Corning Iberica

Sales Office

TEL: + 34 93 363 6900

United Kingdom

Customer Service Center Northern Europe

Sales Office

TEL: + 44 1676 528 000

Dow Corning: Benefit from our experience

As the global leader in silicon-based technology and with more than 60 years of experience as a leading lubricant supplier, Dow Corning provides products, services and business solutions to meet your needs exactly. Whether you need to boost performance, lower costs, or increase customer satisfaction with your home electronic systems, modules and components, we have experts who can help.

LIMITED WARRANTY DISCLAIMER

To the full extent permitted by law, Dow Corning disclaims any and all liability with respect to your use of, or reliance upon, any report, data, procedure, conclusions or opinion contained in the information provided to you. You agree that you have the sole obligation to decide whether information provided by Dow Corning will work in your processes or will be safe and efficacious in your applications. It is your sole responsibility to determine the suitability of any products made by or for you in reliance on the information provided to you. Dow Corning does not make any warranty or representation, express or implied, with respect to the utility or completeness of the information provided to you and specifically disclaims the implied warranties of merchantability and fitness for a particular purpose.

Dow Corning is a registered trademark of Dow Corning Corporation.

Molykote is a registered trademark of Dow Corning Corporation.

© 2006 Dow Corning Corporation. All rights reserved.

Form No: 80-3353-01

*We help you
invent the future.™*

DOW CORNING

www.dowcorning.com