


Engineered elastomer solutions for vehicle systems design

Smart science drives component
durability innovation



Design for process efficiency and performance durability

Meet trend-driven design needs for energy efficiency, greater comfort, safety and sustainability with engineered elastomers from Dow. Our selection of advanced silicone and fluorosilicone rubber elastomers can help you achieve:

- **Energy efficiency** by enabling lightweight design with proven mechanical and environmental resistance
- **Driving comfort** by reducing squeaks; rattles; and noise, vibrations and harshness (NVH)
- **Safety** by improving component durability and safety system reliability
- **Sustainability** with efficient processing and increased service life of components

Choose from a wide range of high-performance engineered elastomers to meet your requirements for efficient processing and durable performance:

- High-consistency silicone rubber (HCR)
- Liquid silicone rubber (LSR)
- Fluorosilicone rubber (FSR)
- Fluoro liquid silicone rubber (F-LSR)

Key performance advantages of these engineered elastomer technologies from Dow include:

- Excellent resistance to fuel, oil and solvents
- Wide service-temperature range from -40 to 316°C (-40 to 600°F)
- Stable electrical insulating properties when exposed to severe-duty service requirements
- Excellent mechanical strength and flexibility with durable resistance to aging, cracking, softening and compression set
- Application-matched choices in hardness, specific gravity, tensile strength, elongation, color and flow properties
- Process-matched compounds and standard



Innovate with smart science

Proven, effective engineered elastomer solutions from Dow can help you meet vehicle system design goals for innovation in process efficiency and performance durability:

Powertrain

- 1 Anti-drainback oil filter valve
- 2 Cylinder head
- 3 Oil pan
- 4 Air intake manifold
- 5 Fuel delivery diaphragms
- 6 EGR valve diaphragms
- 7 Fuel quick-connect seals
- 8 Turbocharger, intercooler hoses
- 9 Radiator seals
- 10 Engine coolant hoses
- 11 Heater hoses
- 12 Transmission seals
- 13 Driveline CVJ boots
- 14 Engine mounts, exhaust hangers

Chassis and brakes

- 15 Gaskets and seals
- 16 Bellows, dust covers, boots

Electrical


- 17 Wire harness connectors
- 18 Coil-to-plug wire insulation
- 19 Spark plug boots
- 20 Ignition cable insulation
- 21 HEV-EV charging cable insulation
- 22 Battery connector seals

Exterior

- 23 Lighting

Safety

- 24 Airbag fabric coatings



Selection guide: Engineered elastomers

APPLICATION			POTENTIAL SOLUTIONS	REGIONAL AVAILABILITY			
Powertrain systems				NA	LA	EMEA	APAC
	Anti-drainback oil filter valve	- Stable mechanical properties - Resistance to engine oils, including synthetics - Resistance to hardening or softening over a wide range of service temperatures	Liquid silicone rubber (LSR):				
			SILASTIC™ 9390-70 Liquid Silicone Rubber	•	•	•	•
			Rubber compounds for fabricated parts:				
	Oil pan gasket	- Good resistance to engine oils, including synthetics - Resist compression set and retain flexibility across service temperature range	XIAMETER™ 21068-V Silicone Rubber	•			
			Rubber compounds for fabricated parts:				
			XIAMETER™ Q4-2918 Silicone Rubber Compound	•			
	Rocker cover gasket	- Good oil resistance - Good compression set resistance and compression stress relaxation	XIAMETER™ Q4-2918LV Silicone Rubber Compound	•			
			Rubber compounds for fabricated parts:				
			XIAMETER™ MX 4108 Silicone Rubber	•	•	•	•
	Air intake manifold gasket	- Oil resistance - Good aging in hot fuel vapors - Good resistance to compression set	XIAMETER™ Q4-2918 Silicone Rubber Compound	•			
			XIAMETER™ Q4-2918LV Silicone Rubber Compound	•			
			XIAMETER™ 24048-V Silicone Rubber	•	•	•	•
	Fuel delivery diaphragms	- Long-term fuel resistance - Good flexibility over a wide range of service temperatures	XIAMETER™ 24057-V HCR Compound	•		•	
			XIAMETER™ 24096-V Silicone Rubber	•			
			XIAMETER™ 24097-V HCR Compound	•		•	
	Exhaust gas recirculation (EGR) valve diaphragms	- Good fuel resistance - Durable flexibility in high service temperatures (200°C)	Cured-in-place gasketing (CIPG):				
			SILASTIC™ RBL-9694-30P Liquid Silicone Rubber	•	•	•	•
			SILASTIC™ RBL-9694-45M Liquid Silicone Rubber	•	•	•	•
	Fuel delivery quick-connector seals	- Fuel resistance - Good flexible in heat/cold - Good permeation resistance - Good compression set resistance and stress relaxation properties - Low swell - High tear strength	Cured-in-place gasketing (CIPG):				
			SILASTIC™ RBL-9694-30P Liquid Silicone Rubber	•	•	•	•
			SILASTIC™ RBL-9694-45M Liquid Silicone Rubber	•	•	•	•
	Fuel delivery quick-connector seals	- Fuel resistance - Good flexible in heat/cold - Good permeation resistance - Good compression set resistance and stress relaxation properties - Low swell - High tear strength	Fluoro-liquid silicone rubber (F-LSR):				
			SILASTIC™ FL 30-9201 Fluoro Liquid Silicone Rubber	•	•	•	•
			SILASTIC™ FL 40-9201 Fluoro Liquid Silicone Rubber	•	•	•	•
	Fuel delivery quick-connector seals	- Fuel resistance - Good flexible in heat/cold - Good permeation resistance - Good compression set resistance and stress relaxation properties - Low swell - High tear strength	SILASTIC™ FL 60-9201 Fluoro Liquid Silicone Rubber	•		•	
			Fluorosilicone rubber compounds (FSR):				
			SILASTIC™ EFX20MHS00 Fluorosilicone Compound	•	•	•	•
	Fuel delivery quick-connector seals	- Fuel resistance - Good flexible in heat/cold - Good permeation resistance - Good compression set resistance and stress relaxation properties - Low swell - High tear strength	SILASTIC™ EFX30MHS00 Fluorosilicone Compound	•	•	•	•
			SILASTIC™ EFX60MLC00 Silicone Rubber	•	•	•	•
			SILASTIC™ FCM 55-1241-FX Fluorosilicone Compound	•			
	Fuel delivery quick-connector seals	- Fuel resistance - Good flexible in heat/cold - Good permeation resistance - Good compression set resistance and stress relaxation properties - Low swell - High tear strength	SILASTIC™ FCM 60-1278-FX FSR Rubber	•	•	•	•
			SILASTIC™ 28075HD-V Fluorosilicone Rubber	•			
			SILASTIC™ 28819-V Fluorosilicone Compound	•			
	Fuel delivery quick-connector seals	- Fuel resistance - Good flexible in heat/cold - Good permeation resistance - Good compression set resistance and stress relaxation properties - Low swell - High tear strength	SILASTIC™ 38640-V Fluorosilicone Rubber	•		•	•
			Fluoro-liquid silicone rubber (F-LSR):				
			SILASTIC™ FL 30-9201 Fluoro Liquid Silicone Rubber	•	•	•	•
	Fuel delivery quick-connector seals	- Fuel resistance - Good flexible in heat/cold - Good permeation resistance - Good compression set resistance and stress relaxation properties - Low swell - High tear strength	SILASTIC™ FL 40-9201 Fluoro Liquid Silicone Rubber	•	•	•	•
			SILASTIC™ FL 60-9201 Fluoro Liquid Silicone Rubber	•	•	•	•
			Fluorosilicone rubber compounds (FSR):				
	Fuel delivery quick-connector seals	- Fuel resistance - Good flexible in heat/cold - Good permeation resistance - Good compression set resistance and stress relaxation properties - Low swell - High tear strength	SILASTIC™ EFX70MLC00 Silicone Rubber	•	•	•	•
			SILASTIC™ 28075HD-V Fluorosilicone Rubber	•			
			Fluorosilicone rubber compounds (FSR):				
	Fuel delivery quick-connector seals	- Fuel resistance - Good flexible in heat/cold - Good permeation resistance - Good compression set resistance and stress relaxation properties - Low swell - High tear strength	SILASTIC™ EFX70MLC00 Silicone Rubber	•	•	•	•
			SILASTIC™ EFX75MLC10 Fluorosilicone Rubber	•	•	•	•
			SILASTIC™ FCM 75-4955 LC Silicone Rubber	•	•	•	•
	Fuel delivery quick-connector seals	- Fuel resistance - Good flexible in heat/cold - Good permeation resistance - Good compression set resistance and stress relaxation properties - Low swell - High tear strength	SILASTIC™ 28075HD-V Fluorosilicone Rubber	•			
			Fluorosilicone rubber compounds (FSR):				
			SILASTIC™ EFX70MLC00 Silicone Rubber	•	•	•	•

APPLICATION		DESIGN NEEDS	POTENTIAL SOLUTIONS	REGIONAL AVAILABILITY			
Powertrain systems (continued)				NA	LA	EMEA	APAC
	Turbocharger, intercooler hoses	- Withstand a wide range of service temperatures - Good resistance to fuel, oil and exhaust gases - Good interlayer adhesion without cracking or peeling - High mechanical strength	Silicone rubber compounds for outer layers:				
			SILASTIC™ HCC 55-1002-NP Silicone Rubber	•	•	•	•
			SILASTIC™ HCC 65-1027-NP HCR Compound	•			
			SILASTIC™ HCC 70-1012-GP Silicone Rubber	•		•	
			SILASTIC™ HCC 70-1031-NP HCR Compound	•			
			Self-adhesive rubber compounds: <i>Intermediate layer:</i>				
			SILASTIC™ HCE 70-4770 SA Silicone Rubber	•	•	•	•
			Fluorosilicone rubber compound for hose liners:				
			SILASTIC™ FCC 55-1047-FX Fluorosilicone Rubber	•	•	•	•
	Radiator seals	- Seal in coolant - Maintain sealing performance from -50 to 200°C and at pressures up to 20 psi - Provide compression gasket for engineered groove	Cured-in-place gasketing (CIPG):				
			SILASTIC™ RBL-9694-30P Liquid Silicone Rubber	•	•	•	•
			XIAMETER™ RBL-2004-70 Liquid Silicone Rubber	•		•	•
	Water coolant hoses and radiator hoses	- Good chemical/solvent resistance - Durable high-temperature performance - Easy processing for calendaring or extrusion	Silicone rubber bases:				
			XIAMETER™ RBB-2100-60 Base	•	•	•	•
			Rubber compounds for fabricated parts:				
			SILASTIC™ HCE 65-1029-NP Silicone Rubber	•			
			SILASTIC™ HCR 65-1030-NP Silicone Rubber	•			
			SILASTIC™ HCE 70-1026-NP Silicone Rubber	•			
			SILASTIC™ 20031-D BLU Silicone Rubber Blue	•			
			SILASTIC™ 20032-D RED Silicone Rubber Red	•			
			SILASTIC™ 20039-D GRN Silicone Rubber Green	•			
	Low-pressure heater hoses	- Good chemical/solvent resistance - Durable high-temperature performance - Easy processing for calendaring or extrusion	Rubber compounds for fabricated parts:				
			SILASTIC™ 27788-Z Silicone Rubber	•	•	•	•
			SILASTIC™ 27790-Z Silicone Rubber	•			
	CVJ boots	- High flex-fatigue life - Durable flexibility over a wide temperature range - Good resistance to lubricants and road contaminants	Rubber compounds for fabricated parts:				
			SILASTIC™ HCM-1102 Silicone Rubber	•			
			XIAMETER™ EHP60MHS01 Silicone Rubber	•		•	
	Engine mounts, exhaust hangers	- High tear strength - Stable mechanical properties - Long-term resistance to extreme heat and cold	Rubber compounds for fabricated parts:				
			XIAMETER™ HCM 75-4731 LC Silicone Rubber	•	•	•	•
			XIAMETER™ 21058-V Silicone Rubber	•			
			XIAMETER™ 24104-V Silicone Rubber	•			
			XIAMETER™ 24140-V Silicone Rubber	•			
			XIAMETER™ 24142-V Silicone Rubber	•			

NOTE: These silicone and fluorosilicone engineered elastomers are proven, effective solutions for vehicle systems design innovation. Contact your Dow representative for product options to meet specialized requirements.

Selection guide: Engineered elastomers

APPLICATION	DESIGN NEEDS	POTENTIAL SOLUTIONS	REGIONAL AVAILABILITY				
Chassis and brake systems			NA	LA	EMEAI	APAC	
	Bellows, dust covers, boots, gaskets, seals	• Good mechanical properties • Tear strength • Weatherability	Rubber compounds for fabricated parts:				
			SILASTIC™ HCM 1102 Silicone Rubber	•			
			XIAMETER™ EHP60MHS01 Silicone Rubber	•		•	
Electrical systems							
	Wire harness connector seal HEV/EV battery connector seals	• Watertight protection • Heat and fluid resistance • Easy assembly with self-lubricating properties • High mechanical strength • Easy processing • Watertight protection • Heat and fluid resistance • Easy assembly with self-lubricating properties • High mechanical strength • Easy processing	Rubber compounds for fabricated parts:				
			SILASTIC™ WS 190-60-01 Silicone Rubber	•		•	
			XIAMETER™ 20003-V Silicone Rubber	•			
			XIAMETER™ 20018-V Silicone Rubber	•			
			XIAMETER™ 22013-V Silicone Rubber	•			
			XIAMETER™ 23010-V Silicone Rubber	•			
			XIAMETER™ 23023-V Silicone Rubber	•			
			XIAMETER™ 23077-V Silicone Rubber	•			
			XIAMETER™ 23084-V Silicone Rubber	•			
			XIAMETER™ HCM 18-1265 Silicone Rubber	•			
			XIAMETER™ HCM 18-1303 Silicone Rubber	•			
			Liquid silicone rubber (LSR):				
			SILASTIC™ 9201-50 Liquid Silicone Rubber	•	•	•	•
			SILASTIC™ 9202-30 Liquid Silicone Rubber	•		•	•
			SILASTIC™ 9202-50 Liquid Silicone Rubber	•	•	•	•
			SILASTIC™ 9204-30 Liquid Silicone Rubber	•	•	•	•
			SILASTIC™ 9204-50 Liquid Silicone Rubber	•		•	•
			SILASTIC™ LTC 9402-50 Liquid Silicone Rubber	•		•	
			SILASTIC™ LC40-9001 Liquid Silicone Rubber	•			
			SILASTIC™ LC30-9422 Liquid Silicone Rubber	•			
			Fluorosilicone rubber compounds (FSR):				
			SILASTIC™ FCM 35-1244 Fluorosilicone Compound	•			
			SILASTIC™ FCM 40-1174 Fluorosilicone Compound	•			
			SILASTIC™ FCM 40-1195 Fluorosilicone Compound	•			
	Distributorless ignition (DLI) plug wire	• Weatherability • Wide range of service temperatures	Rubber compounds for fabricated parts:				
			XIAMETER™ 29046B-T Silicone Rubber	•			
	Spark plug boots	• Electrical insulation for high voltages • High service temperatures	Rubber compounds for fabricated parts:				
			XIAMETER™ 23004-V Silicone Rubber	•			•
			XIAMETER™ 25065-V Silicone Rubber	•			
	Ignition cable insulation	• Electrical insulation for high voltages • High service temperatures	Rubber compounds for fabricated parts:				
			XIAMETER™ 23004-V Silicone Rubber	•			•
	Hybrid and electric vehicle charging cable insulation	• Reliable electrical insulation • High mechanical strength and flexibility • Low flammability • Weatherability	Rubber compounds for fabricated parts:				
			SILASTIC™ RBC 7100-60 Compound	•	•	•	•

NOTE: These silicone and fluorosilicone engineered elastomers are proven, effective solutions for vehicle systems design innovation. Contact your Dow representative for product options to meet specialized requirements.

APPLICATION		DESIGN NEEDS	POTENTIAL SOLUTIONS	REGIONAL AVAILABILITY			
Exterior systems				NA	LA	EMEA	APAC
	Lighting - secondary optics	- Optically clear - Good mold flow - Excellent feature reproduction - Lighter than glass	SILASTIC™ MS-1001 Moldable Silicone	●	●	●	●
			SILASTIC™ MS-1002 Moldable Silicone	●	●	●	●
			SILASTIC™ MS-4002 Moldable Silicone	●	●	●	●
Safety systems							
	Airbag coating and sealing	- High performance at lower coating weights - High thermal resistivity - Excellent adhesion to PET and PA - Foldability - Flexibility	Coatings				
			Flat fabric:				
			SILASTIC™ LCF 3600 Coating	●		●	●
			One-piece woven (OPW)				
			SILASTIC™ LCF 3760 Liquid Silicone Rubber	●		●	●
			SILASTIC™ 3715 Curing Agent	●	●	●	●
			Seam sealant				
			SILASTIC™ SE 6777 LSR	●	●	●	●

NOTE: These silicone and fluorosilicone engineered elastomers are proven, effective solutions for vehicle systems design innovation. Contact your Dow representative for product options to meet specialized requirements.





Learn more: contact us

To learn more about how our engineered elastomers can help meet challenging design needs in automotive and transportation applications, contact your Dow Technical Representative, visit www.dow.com.



Sustainable design solutions

Enhance your vehicle systems design sustainability with silicone and fluorosilicone engineered elastomers from Dow. These advanced elastomer technologies can be custom-formulated for specified performance characteristics, regulatory standards and specialized process requirements. They are proven, effective solutions that can resist degradation from alternative fuels, synthetic oils and aggressive fluids; withstand increased operating temperatures; help reduce material consumption in lighter-weight vehicles; and aid local production of global vehicle platforms.

More Dow smart science

In addition to the silicone rubber materials including: liquid silicone rubber, fluorosilicone rubber, high consistency rubber, fluoro liquid silicone rubber and cured-in-place gasketing featured in this selection guide, Dow also offers more smart science for vehicle system design innovation with our DOWSIL™ adhesives and sealants.

Images: Cover - dow_40962386523; Page 2 - dow_42007059343; Page 3 - dow_40644849358, Page 4 - dow_40254657384, dow_40145787864, dow_40145731590, dow_40145801645, dow_40176189186, dow_40365049392, dow_40387783136; Page 5 - dow_40254480915, dow_40962782708, dow_40387784752, dow_40387792891, dow_40384221728, dow_40800865506; Page 6 - dow_39921101471, dow_40176190201, dow_40354046238, dow_40176179282, dow_40354036491, dow_40611866157, dow_39921102247; Page 7 - dow_40370577492, dow_40388832169, dow_56386207889; Page 8 - dow_40145808550, dow_40962211859,

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW WEBSITE AT WWW.DOW.COM, OR FROM YOUR DOW SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CUSTOMER SERVICE.

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

© 2019 The Dow Chemical Company. All rights reserved.

S2D 93193/E27430

Form No. 80-8173-01 D